

MIRO-L100

MIRO-L110

Compact mobile router



MIRO – simply industrial

Compact. Easy. Secure.

The MIRO series from INSYS provides secure and stable routing in a very compact device for an attractive price. The mobile routers are suitable for secure Internet connections and remote maintenance, and impress with their high system stability, durability and ease of use.



Highly compact design

Easy integration into automatic dispensing machines and digital signage solutions, also available as module



Easy remote access & updates

Plug & play connection of VPN service and central device management



Flexible mounting

Top-hat rail mounting for control cabinets/small distribution boards and wall mounting



Ethernet and I/O

Ethernet connection and configurable digital input/output



High level of IT security

Hardened operating system, extensive monitoring and security functions



Professional router operating system

Extensive VPN and routing functions with easy usability

MIRO-L100 MIRO-L110



Technical Data

Mobile communication	
Frequency bands, data rates	4G/LTE*: 700, 800, 900, 1.800, 2.100, 2.600 MHz (bands 1, 3, 7, 8, 20, 28A); LTE Cat. 1 (DL: max. 10 Mbps, UL: max. 5 Mbps)
MIRO-L100 & MIROdul-L100	3G/UMTS/HSPA: 900, 2.100 MHz (bands 1,8), HSDPA/HSUPA (DL: max.42 Mbps, UL: max.5,7 Mbps) 2G/GPRS/EDGE: 900, 1.800 MHz, GPRS/EDGE Class 12 (DL: max. 296 kbps, UL: max. 237 kbps)
Frequency bands, data rates	4G/LTE*: 700, 1700/2100 (AWS), 1900 MHz (bands 2, 4, 12), LTE Cat.1 (DL:max. 10 Mbps, UL max. 5 Mbps)
MIRO-L110 & MIROdul-L110 (North America)	3G/UMTS/HSPA: 850, 1700/2100 (AWS), 1900 MHz (bands 2, 4, 5), HSDPA/HSUPA (DL:max 42 Mbps, UL:max 5,7 Mbps)
Antenna connection	1x SMA female
SIM	Slot for 1 Mini-SIM card (2FF), locked Provider redundancy with multi-roaming SIM cards (see section "Suitable accessories")
Cellular Status	Signal field strength, RSSI, RSCP / Ec/No, RSRP / RSRQ, Cell-ID, Location-ID
Hardware interfaces	
Ethernet ports	1 x RJ45 shielded, 10/100 MBit/s, Full/half duplex, Auto MDI-X, 1.5 kV isolation voltage
Ethernet function	link up/down detection
I/Os	1 digital input or output, configurable: Input low active (contact input) or output open drain (24 V / 50 mA)
Displays (LEDs)	Power, WAN (Internet connection), Info (configurable), Signal (mobile communication)
Network	
Network functions	5 local IP networks, IP static/DHCP,TCP, UDP, IPv4, IPv6, NTP, DHCP, DNS, HTTP/S, ARP, SSH, 802.1Q VLAN incl. tags and trunk ports
Service	DHCP Server v4/v6 per IP network, DHCP relay, NTP server, DNS, DynDNS, IPv6 Router Advertiser
Routing	Static routing, routing priority, RSTP, dynamic routing (OSPF, BGP, RIPv1, RIPv2, RIPng)
Connection check	Periodic, ping/icmp, DNS request, link up/down
DSL	external DSL modems: PPPoE
NAT/PAT	SNAT/DNAT (masquerade, netmapping, port forwarding, IP forwarding) unlimited number of rules
VPN	
icom Connectivity Suite	Supports VPN service for remote maintenance, remote access and M2M-communication
OpenVPN	Client/server, several parallel tunnels, server with up to 20 clients, tls-auth/tls-crypt, dead peer detection (DPD)
OpenVPN encryption	Blowfish 128 Bit, DESX 192 Bit, DES 64 Bit, DES EDE 128 Bit, DES EDE3 192 Bit, AES 128-256 Bit, RC2 40-128 Bit, IDEA 128, CAST5 128 Bit, SHA1, SHA 224-512
IPsec	IKEv1, IKEv2 (automatic, fix), several parallel tunnels, pre-shared keys, certificates, tunnel mode, transport mode, dead peer detection (DPD)
IPsec encryption	DES EDE3 192 Bit, AES 128-256 CBC/GCM, SHA1, MD5, SHA 256-512, DH-Group 1-31 (Diffie-Hellman 768 - 25519), ChaCha20-Poly1305
GRE	GRE via IPsec, point-to-point, multipoint
PPTP	PPTP client/server; PAP/CHAP/MS CHAP/MS CHAP V2; MPPE 40-128
Dynamic VPN	Dynamic multipoint VPN (GRE, IPsec, NHRP, EIGRP, OSPF, RIPv1/v2, BGP)
IT security	
Authentication	Pre-shared key, X.509 certificates, RADIUS, access rights (read, write, status)
Firewall / netfilter	IP filters (stateful firewall) also in VPN tunnel; packet filter: TCP, UDP, ICMP, ESP, AP, GRE; MAC filter; pre-defined firewall rules can be activated
Security	Bootimg signed firmware, HTTP/HTTPS attack prevention; response upon events: configuration change, link up/down, restart, login attempt, netfilter violation, password hashing

MIRO-L100

MIRO-L110



Technical Data

Events & Actions	
Event & Action Handler	Notification, alarming, diagnosis, attack detection, fault handling, operation and commissioning logic
Events / alarms (selection)	Change: digital input, Ethernet port, WAN chain, profile status, supply input (with MRX), cellular field strength; timer expired, firewall violation, login attempt detection, pulse sequence on digital input, counter, netfilter rule
Event-triggered actions (selection)	Messages via e-mail, SMS (only cellular variants), SNMP traps, MCIP; switch profile, switch connection, change modem state, start timer, switch output or pulse sequence, activate firmware, reset
Monitoring and Management	
Monitoring	SNMP traps and agent, configurable system logs, remote syslog, link up/down detection, netfilter violation
Certificate management	SCEP, CRL
icom Router Management	Supports central router management for FW updates, configuration management, connection monitoring mass rollout, certificate management, available as public/private, cloud (server) installation or onPremises
Administration	
Configuration	Web Interface HTTP(S) with session management, command line interface (CLI), Telnet, SSH, configuration profiles as ASCII and binary file, ample configuration profiles event-triggered, REST API
Diagnosis tools	Ping/icmp, tcpdump, traceroute, DNS lookup, AT commands, port mirroring
FW update	Incremental, failsafe, update server (HTTP, FTP, HTTPS, FTPS), icom Router Management (WebSocket)
System time	NTP client and server, buffered real time clock
Help	Web interface: inline help, online help; example profiles, plausibility check, Configuration Guides
Supply	
Voltage	12 ... 24 V DC (\pm 20% 9,6-28,8V)
Terminals	3-pol. push-in terminal connectors, rigid/flexible conductors up to 1,5 mm ²
Power consumption	Typical approx. 1,5 W, max. 5,0 W
Ambient conditions	
Dimensions	MIRO: 26 x 77 x 99 mm (W x D x H) MIROdul: ca. 82 x 70 x 17 mm (W x D x H)
Weight	MIRO: 94 g MIROdul: 42 g
Mounting	MIRO: DIN rail mounting, horizontal pitch (HP) on DIN rail: Switch cabinet: 1.5 HP, depth on DIN rail 92 mm Small distribution board: 4.5 HP, requires additional lateral DIN rail holder (accessory) MIRO/MIROdul: screw mounting via holes in the housing/module
Operating temperature	-40 +75°C ²
Humidity	0 ... 95% (non-condensing)
IP rating	Housing: IP40
Approvals & Standards	
Certifications	MIRO-L100 / MIROdul-L100: CE MIRO-L110 / MIROdul-L110: FCC Part 15 Class B, IC
EMC	Emission: EN 55032 Class B, EN 61000-6-3; Immunity: EN 55024, EN 61000-6-2
Safety	IEC/EN 62368-1
Environmental conditions	Vibration/shock as per PLC standard DIN EN 61131-2 Temperature tests as per EN 60068-2-1, EN 60068-2-2, EN 60068-2-14, EN 60068-2-30
Operating time	MTBF > 1.000.000 h (25°C), according to SN 29500 (according to IEC 61709)

* Please check the availability of the Mobile communication frequencies in the planned operating area.
Above specified frequencies are currently used in Europe, Middle East, Africa and, to some extent, in the Asia-Pacific region and South America.

² +70°C ... +75 °C: extended temperature range (refer to www.insys-icom.com/en-extended/)

MIRO-L100

MIRO-L110

Order Numbers and Accessories

Available Variants

Product description	Features	Art. nr.
MIRO-L100	LTE router, 1x ETH, 1 dig. input/output (configurable)	10022846
MIRO-L110	LTE router (North America variant), 1x ETH, 1 dig. In-/Output (configurable)	10022847
MIROdul-L100	LTE router module, 1x ETH, 1 dig. input/output (configurable)	10023100
MIROdul-L110	LTE router module (North America variant), 1x ETH, 1 dig. In-/Output (configurable)	10023101

Suitable accessories

Product description	Description	Art.-nr
Magnetic Antenna LTE/UMTS/GSM SMA	Magnet mounting, height 72 mm, 3 m cable, SMA (m), IP rating IP65	10019504
Outdoor Wall Antenna LTE/UMTS/GSM	Wall mounting incl. bracket, height 220 mm, 5 m cable, SMA (m), IP rating IP65	10020596
Allround Antenna 5G/LTE/UMTS/GSM SMA	Screw or wall mounting, incl. steel angle, height 82 mm, 5 m cable, SMA (m), protection class IP66	10022961
Antenna extension cable 5 m SMA	Device connector: SMA (f), antenna connection: SMA (m)	10015193
Antenna extension cable 10 m SMA	Device connector: SMA (f), antenna connection: SMA (m)	10018607
Antenna extension cable 15 m SMA	Device connector: SMA (f), antenna connection: SMA (m)	10000735
Power supply 24V 15W	Power supply unit for DIN rail, wide-range input voltage ACDC protection against short circuit / overload / over voltage	10022848
Wall power supply 24V 25W international	Power supply AC/DC with mains plug, suitable for desktop use, wide input, voltage range, protection against short circuit/overload/over voltage	10022849
Din rail holder set MIRO	Additional DIN rail holder for flat mounting in small distribution boards incl. screws	10023140
icom Connectivity Suite - VPN	Supports VPN service for remote maintenance, remote acces and M2M communication; www.insys-icom.com/en-VPN/	various
icom Connectivity Suite - M2M SIM	Industrial SIM cards, multi-roaming, pooling, management portal www.insys-icom.com/en-SIM/	various
icom Router Management	Supports central router management for FW updates, configuration management, connection monitoring, container updates, mass rollout, certificate management; available as public/private cloud (server) installation or onPremises www.insys-icom.com/en-IRM/	various

© INSYS 211012 - Subject to technical changes and correction